

Operation and maintenance

Inspection and maintenance performed as required or at least with the above time interval. Inspection documented

	General	Cleaning / Maintenance	Interval	Recommendation
Aluminium Coated / anodized surface	Maintenance of powder coated or anodized aluminium surfaces will be limited to simple cleaning	Simple cleaning with water and neutral detergent, such as dishwashing liquid. Use a soft brush or soft sponge. Rinse with clean water.	Every 6 months Exposed areas*: Every 3 months	Finishing with wax to protect the surface. The surface becomes more resistant to dirt and will look cleaner and tidier. Prevents fading of the surface. Every 2 years.
Glass	Simple cleaning as required	Simple cleaning with water and neutral detergent, such as dishwashing liquid. Use a soft brush or soft sponge. Rinse with clean water.	Every 6 months Exposed areas*: Every 3 months	
Brackets / Moving parts	An element has to be fully functional and in good working condition. In addition to daily use, test function with fixed intervals for necessary maintenance and to comply with possible legal requirements.	Lubricate with acid free oil / grease. Simple cleaning without water.	1 annually Exposed areas*: Every 6 months	Always keep bearings and fittings free from dirt.
Gaskets	Simple cleaning. Dirt removal	Lubricate with silicone oil. Simple cleaning. Wipe the dirt	1 annually	Silicone causes sealing to retain flexibility and to close tightly.